

INDEPENDENT

BATTERY CERTIFICATE



CERTIFICATE NUMBER: B2A2899F-FA69-412B-88FA-EF2A981966AF

VEHICLE

BRAND: MG Automotive
MODEL: MG4 Electric - 64,0 kWh

MILEAGE: 16,712 mi
VIN: LSJWH4094PN271101

EXECUTED BY: Henley Cars Ltd t/a Car360

DATE AND TIME:
23.12.2025, 12:00:25

RESULTS

STATE OF HEALTH (SOH)

97.3 %

ENERGY 60kWh | 62kWh




WLTP RANGE 272mi | 280mi

RATING

BENCHMARKING

How does your vehicle compare to comparable vehicles?



CHECKS

- Battery Management System (BMS) ✓
- Battery Sensor ✓
- Battery Measurements ✓
- Battery Cell Voltages ✓
- Vehicle Communication ✓



EVALUATION

EXCELLENT HEALTH - NO ABNORMALITIES DETECTED

Based on the detailed battery diagnostics performed with the AVILOO FLASH Test, we hereby certify that the drive battery of this vehicle is in excellent condition.

The drive battery is therefore officially AVILOO Certified.

Dr. Marcus Berger, CEO



ENERGY

	Gross	Net (Nominal)	Usable
Current:	62.2kWh	60.0kWh	57.5kWh
New:	64.0kWh	61.7kWh	59.1kWh

RANGE

	WLTP	Typical
Current:	423-272mi	196mi
New:	435-280mi	201mi

EXECUTION PROTOCOL

	12:00:21
AVILOO Box connected.	
FLASH Test started.	✓
Starting data acquisition.	✓
Vehicle detected.	✓
Finished data acquisition.	✓
Analyzing data.	✓
Analysis completed.	✓

SENSORS

Voltage Sensor	✓
Current Sensor	✓
Temperature Sensors	✓
Cell Voltage Sensors	✓

BMS

	Value	Status
BMS State of Charge (SoC)*:	5%	
SoC calculation accuracy:		✓
BMS State of Health (SoH)*:	98%	
SoH calculation accuracy:		✓

MEASUREMENTS

	Min	Max	Delta	Status
Battery Temperature	5.5°C	6.0°C	0.5°C	✓
Cell Voltage	3.430V	3.444V	13mV	✓
Pack Voltage	357.8V			
Average Current	-3.2A			

*The values shown here were not calculated by AVILOO but correspond to the values read out from the battery management system (BMS) and were calculated by the manufacturer. AVILOO therefore assumes no liability for their accuracy.

DISCLAIMER: The test result includes the currently calculated state of health (SoH) of the drive battery. The determination is based on data provided by the vehicle. These are evaluated by AVILOO's algorithms using statistical and analytical models. Manipulation of the data in the control unit leads to an incorrect result. The indicated SoH has a technically induced fluctuation range (deviation) of no more than 3% in at least 95% of reference measurements. It should be noted that this tolerance applies to the SoH determination at the cell level and not to the SoH of the entire battery. This is because the state of charge of individual cells may vary, which can negatively affect the current SoH of the battery. However, this can be compensated by the Battery Management System (BMS) or during a calibration. The result reflects the condition of the battery at the time of the test. No conclusions can be drawn about the future state of health of the battery from this. Statements about mechanical damage or external influences are not part of this diagnosis.